

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1386-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		iN-I COMPI (*=N/A or A/E=exi	IEDIATE USE LIANCE full in-use; h. / evap. iate in-use)	FUEL TYPE			
2007		LDT: 6001-8500# GVW, 5751-	USEPA Bin 4	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2 Unleaded)			
	7FMXT05.44D7	8500# ALVW	Counted as ARB LEV2 ULEV	120K	150K	*	<u> </u>	Officaded)			
No.	ECS &	SPECIAL FEATURES		EVAPORATIVE FAMILY (EVAF)				DISPLACEMENT (L)			
1	2TWC,	2HO2S(2), SFI, OBD(F)	7FMXR0	7FMXR0240NBR							
		•	E	•				5.4			
•		•	# 1	*							
*		•		•				<u></u> .			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-1386 dated November 14, 2006.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE [g/ml]		NMOG @ CH4 R	NMOG @ RAF=* CH4 RAF = *		HCHO=for	ane; NMOG≕r maldehyde; Pi RL [g/mi]≑runn	M=particula	ate matter; F NRVR Inicali	RAF≕reacu Ion dispen:	(vity adjus) sed)=on-bi	ment racti bard refue	ding vapor re	covery; g=gr		
CERT			NMHC	NMHC STD	mi=mile; K	CO-formatchenyde; PM=particulate fraint; RAF=leatinty applications RE g/mi]=running loss; ORVR g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram intenset; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure									
0.055	0.055	CERT	CERT	[g/mi]		[g/mi]		x [g/mi] STD	CEF		STD	CERT	STD	CERT	STD
0.035	0.033	[g/mi]	[g/mi]		CERT	STD	CERT	310	- CL		-	*		*	
7.7	@ 50K	*	•	*	<u> </u>				-		44	-	0.01	0.03	0.05
	@ UL	0.058	*	0.070	1.3	2.1	0.04	0.04			11.			0.00	+
- 100 A	@ 50°F & 4K	•		*	*	• _	•	. *	*		*				
CO [g/ml]					iOx [g/ml] CO [g/ posite) (compo							NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
	@ 20°F & 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	4,9	SFT	P @ 50000 miles	0.07	1.49	•	*	•	*	2.2	13.2	•	*	1.0	4.4
STD	12.5	SFTP	@ 120000 miles	0.07	2.09	•	•	*	*	2.4	19.3	*		1.2	6.4
Evaporative Family (gr		3-Days Di (gran	lurnal + Ho ns/test) @ l		2-Days Diu (grams	rnal + Hot Soak /test) @ UL			Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/gallon) @ UL			
		CERT	s	TD CERT			STD	CERT		STD	D CERT		STD		
		0.36	0	,90 0.33		<u> </u>	1.15	5 0.00		0.05		0.07		0.20	
/FMARU24UNDR		+		* 4		*		•			*		*		
*						-								•	
*		*	- -	*	*	 	*		-	4		+		*	

^{*=} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=xid/sting catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2007 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMP (*=N/A or A/E=ex	IEDIATE USE LIANCE full In-use; h. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
FORD	F-150 PICKUP 2WD	7FMXR0240NBR	1	5.4	*	·	SFTP	Full
FORD	F-150 PICKUP 4WD	7FMXR0240NBR	1	5.4	•	*	SFTP	Full
FORD	F-150 SUPER CREW PICKUP 2WD	7FMXR0240NBR	1	5.4	•	*	SFTP	Full
FORD	F-150 SUPER CREW PICKUP 4WD	7FMXR0240NBR	1	5.4	•	*	SFTP	Full
LINCOLN	MARK LT 2WD	7FMXR0240NBR	1	5.4	•	•	SFTP	Full
LINCOLN	MARK LT 4WD	7FMXR0240NBR	1	5.4	*	•	SFTP	Full
FORD	F-150 PICKUP STX 2WD	7FMXR0240NBR	1	5.4	•		SFTP	Full